

OPTIC 10 LED GLOBE WITH DIMMABLE DRIVER

Model No.	Dimension	
UOPTIC10-WH (White)	D50mm x H73mm	
UOPTIC10-WW (Warm White)	D50mm x H73mm	



Specification Chart		
	White	Warm White
Luminous Flux	900 lm	720 lm
Luminous Efficiency	90 lm/w	72 lm/w
Colour Temperature	5600K	3000K
Colour Rendering Index	75 CRI	90 CRI
Wattage	10W	10W
Beam Angle	60 degree	60 degree
Rated Lamp Life	50,000hrs	50,000hrs

FEATURES:

- . Suitable replacement for the traditional Halogen or CFL down light
- . Saves up to 70% electricity cost
- . Long life (Warranty 3 years)
- . UV free, ROHS compliant
- . Anodised Aluminium body
- . High transmissive PMMA Lens
- . High powered Bridgelux USA LED COB light source
- . High efficiency LED SAA approved LED driver with 1.2M flex & plug
- . Fully dimmable with trailing edge & universal dimmers, C-Bus compatible
- . Light output comparable to 12V 50W Halogen

United Global Enterprises

11 Harper St, Abbotsford Vic 3067 www.ugelighting.com.au sales@unitedglobal.com.au

Ph: 9415 7992 Fax: 9415 7991